


Burner Gas Hob



VTL-PRO-GK09030S

2.00 mm kalınlıkta standart üst tabla
Standard 20/10 mm top thickness



Model Model	Ürün Adı Description	 W	Ölçü / Ağırlık Dimensions / Weight mm/kg	Paketli Ölçü / Ağırlık Pack. Dim. / Gross Weight mm/kg
VTL-PRO-GK09030S	6 Brülörlü Gazlı Ocak 6-Burner Gas Hob	55.000	1200x900x850 38	1300x1000x950 46

General Specifications

- Stainless steel body
- Monoblock worktop
- Safety component and thermocouple
- Pilot flame burners
- Cast iron removable top pan grids
- Double crown brass burners
- High performance and low-emission gas burners
- Usable for countertop or with base cupboard
- Easy to clean through rounded corners worktop
- Lpg or natural gas

Aisi 304 stainless steel structure, 2 mm thick worktop
6 high-power burners, with double cast iron crown
front open support
Burners with pilot flame and thermocouple safety valve
enamelled cast iron support grates with increased rigidity
Dimension: 1200 x 900 x 850
Total power 55 kW

Smooth Chrome Gas Fry-Top



> VTL-PRO-GPI9020SC

2.00 mm kalınlıkta standart üst tabla
Standard 20/10 mm top thickness



Model Model	Ürün Adı Description	W	Ölçü / Ağırlık Dimensions / Weight mm/kg	Paketli Ölçü / Ağırlık Pack. Dim. / Gross Weight mm/kg
VTL-PRO-GPI9020SC	Smooth Chrome Gas Fry-Top	16.500	800x900x850 68	850x950x900 76



Düz
Smooth

General Specifications

- > Stainless steel body
- Monoblock worktop
- Safety component and thermocouple
- Pilot flame burners
- Removable oil drawer
- Piezoelectric ignition system
- High performance and low-emission gas burners
- Usable for countertop or with base cupboard
- Easy to clean through rounded corners worktop
- Lpg or natural gas

Worktop 20/10 mm
Stainless steel Aisi 304 2mm thick
Open cabinet with height-adjustable legs
Solid cast iron hob minimum 15 mm thick with chrome layer minimum "50 µ"
Baking surface minimum 770x740 mm
Temperature control with thermostatic valve up to + 300°C
Safety thermostat with thermocouple
Dimension: 800 x 900 x 850
Gas power 16.5kW

Double Gas Fryer



> VTL-PRO-GFP9020S

2.00 mm kalınlıkta standart üst tabla
Standard 20/10 mm top thickness



Model Model	Ürün Adı Description	W	lt.	Ölçü / Ağırlık Dimensions / Weight mm/kg	Paketli Ölçü / Ağırlık Pack. Dim. / Gross Weight mm/kg
VTL-PRO-GFP9020S	Double Gas Fryer	38.000	2x25	800x900x850 58	850x950x900 66

Genel Özellikler / General Specifications

- > Stainless steel body
- Safety limit thermostat
- Safety component and thermocouple pilot flame burners
- Oil drainage tap
- Basket hanger for oil straining after frying processes
- Up to 190 °C, adjustable 8-level temperature control with pilot flame
- Easy to clean through rounded corners worktop
- Lpg or natural gas

Capacity: 2 x 25 liters
Closed cabinet with 2 hinged doors
Tank dimension: 300x315x120 mm
Thermostatic temperature control in the minimum range +90/+190°C
tanks with used oil disposal valve and filter container
Dimension: 800x900x850mm
Power 38 kW